



06000R Motor Oil 10W-50 High Performance Racing

Document version: 11 May 2024



Description

This premium synthetic high performance racing motor oil of absolute top quality has been specially developed for engines with natural aspiration or turbocharging. This motor oil is specially formulated for High Performance, multi-valve engines and offers excellent protection against friction whilst ensuring a superior lubrication film at high revolutions.

According to the specifications of

ACEA A3/B4
API SM

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001R	1 L	6	450
06020R	20 L	1	30
06060R	60 L	1	6
06205R	205 L	1	2
06999R	1000 L	1	-
P06000R	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.855	kg/l
Viscosity	10W-50	
Kinematic Viscosity at 40°C	128	mm ² /s
Kinematic Viscosity at 100°C	20	mm ² /s
Viscosity Index	179	
Dynamic Viscosity at -30°C	6300	mPa.s
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base Number	10.2	mgKOH/g
Sulphated Ash	0.9	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.