



86000CBL Coolant Premium Longlife -40°C G12+ Ready to Use Clear / Blank

Document version: May 11, 2024



Description

This transparent Long Life OAT silicate-free coolant is of very high quality and has been specially developed for protection of non-ferrous metals such as aluminium and magnesium. This coolant is ready to use.

According to the specifications of

ASTM D3306
DAF 74002
Ford ESE-M97B49-A / WSS-M97B44-C / WSS-M97B44-D
GM/Opel 1940 656 / 6277M
MAN 248 / 324 SNF
MB 326.3
Paccar 74002
Renault 41-01-001
VW TL 774D G12+ / 774F G12+
Volvo No. 260 / VCS

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
86001CBL	1 L	6	450
86005CBL	5 L	4	112
86020CBL	20 L	1	30
86060CBL	60 L	1	6
86205CBL	205 L	1	2
86999CBL	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.07	kg/l
Colour	blank	
Frost Protection	-40	°C
Boiling Point	108	°C
Copper Corrosion	3	

These characteristics are typical of current production. Variations in these characteristics may occur.