



06000PS Motor Oil 0W-40 Pro Street C3

Document version: 11 May 2024



Description

This premium synthetic fuel economy 'MID SAPS' engine oil has been specially developed for petrol and diesel engines with or without a turbocharger. Due to its good thermal and oxidation stability together with excellent protection against wear and corrosion, it offers optimum engine protection. This MPM Motor Oil 0W-40 Pro Street C3 is suitable for passenger cars and light commercial vehicles equipped with an exhaust after-treatment system.

According to the specifications of

ACEA C3
API CF / SN

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001PS	1 L	6	450
06020PS	20 L	1	30
06060PS	60 L	1	6
06205PS	205 L	1	2
P06000PS	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	ASTM D4052
Viscosity SAE	0W-40		
Kinematic Viscosity at 40°C	75.8	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	13.6	mm ² /s	ASTM D445
Viscosity Index	185		ASTM D2270
Dynamic Viscosity at -30°C	6600	mPa.s	ASTM D5293
Flashpoint COC	218	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97
Total Base Number	7.5	mgKOH/g	ASTM D2986
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.