



65000H Heavy Duty Grease

Document version: 11 May 2024



Description

Heavy duty grease is a high-performance Lithium-Calcium grease. This high quality mineral base oil in combination with special EP additives and polymers prevent metal-to-metal contact, reducing friction and wear under extreme conditions. It provides a stable and adherent lubricant film with outstanding water-resistance properties, even under high load conditions. MPM Heavy Duty Grease covers a wide range of usage including off-road and construction applications such as bucket pins, chassis points and heavily loaded plain bearings in shovel loaders and other equipment. It is also suitable for certain 2-way centralised lubrication systems and as fifth wheel grease.

According to the specifications of

DIN 51825
KP2K-20

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
65000H	0.4 kg	12	-
65001H	1 kg	6	-
65005H	5 kg	1	-
65018H	18 kg	1	-
65050H	50 kg	1	-
65185H	185 kg	1	-

Standard analyses

TEST	VALUE	METHOD
Colour	green	
NLGI Classification	2	
Kinematic Viscosity at 40°C	600	mm ² /s
Temperature Range	-20 / 120	°C
Peak Temperature	140	°C
Soap Thickener	Lithium-Calcium	

These characteristics are typical of current production. Variations in these characteristics may occur.