



04000A Motor Oil 10W-40 Super High Performance Diesel Truck

Document version: 11 May 2024



Description

This high-grade semi synthetic motor oil has been specially developed for diesel engines of commercial vehicles. In addition this motor oil has been formulated to make long oil-change intervals possible and to prevent bore polishing.

According to the specifications of

ACEA B3 / B4 / E7
API CF-4 / CG-4 / CH-4 / CI-4
Allison C4
Cummins CES 20076 / CES 20077 / CES 20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
MAN M 3275
MB 228.3
MTU Type 2
Mack EO-M Plus / EO-N
Renault RLD / RLD-2
Volvo VDS-3

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 04020A | 20 L | 1 | 30 |
| 04060A | 60 L | 1 | 6 |
| 04205A | 205 L | 1 | 2 |
| 04999A | 1000 L | 1 | - |
| P04000A | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|--------|--------------------|
| Density at 15°C | 0.867 | kg/l |
| Viscosity | 10W-40 | |
| Kinematic Viscosity at 40°C | 86 | mm ² /s |
| Kinematic Viscosity at 100°C | 13.1 | mm ² /s |
| Viscosity Index | 153 | |
| Dynamic Viscosity at -25°C | 5900 | mPa.s |
| Flashpoint COC | 243 | °C |
| Pourpoint | -42 | °C |
| Total Base Number | 11.9 | mgKOH/g |
| Sulphated Ash | 1.9 | mass% |

These characteristics are typical of current production. Variations in these characteristics may occur.