



05000V Motor Oil 0W-30 Premium Synthetic A5/B5

Document version: 11 May 2024



Description

This premium synthetic fuel conserving motor oil has been developed for petrol and diesel engines equipped with an exhaust gas after-treatment system. This SAE 0W-30 motor oil with the Volvo VCC 95200377 specification is mandatory for various Volvo engines and is the factory recommendation for Honda and Mazda engines where SAE 0W-30 with ACEA A5/B5 is required.

Application manual

According to the specifications of

ACEA A5/B5
API CF / SN
Volvo approval VCC 95200377

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001V	1 L	6	450
05005V	5 L	4	112
05020V	20 L	1	30
05B20V	20 L	1	-
05060V	60 L	1	6
05205V	205 L	1	2
05999V	1000 L	1	-
P05000V	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.860	kg/l	
Viscosity SAE	0W-30 0W-30		
Kinematic Viscosity at 100°C	10	mm ² /s	
Viscosity Index	174		
Flashpoint COC	200	°C	
Pourpoint	-40	°C	

These characteristics are typical of current production. Variations in these characteristics may occur.