



## 02000B Motor Oil 10W-30 Multi Grade

Document version: May 6, 2024



### Description

This high-tech multi-grade motor oil has been developed for the lubrication of four stroke petrol- and diesel engines that are naturally aspirated and turbocharged. This motor oil provides total engine protection and excellent cold-cranking properties.

### According to the specifications of

ACEA A3/B4  
API CF / SN

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
02001B	1 L	6	450
02004B	4 L	4	112
02005B	5 L	4	112
02020B	20 L	1	30
02060B	60 L	1	6
02205B	205 L	1	2
02999B	1000 L	1	-
P02000B	1 L	1	-

### Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.873	kg/l	ASTM D4052
Viscosity	10W-30		SAE
Kinematic Viscosity at 40°C	78.3	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	11.9	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	147		ASTM D2270
Flashpoint COC	220	°C	ASTM D92
Pourpoint	-33	°C	ASTM D97
Total Base Number	10.1	mgKOH/g	ASTM D2986

These characteristics are typical of current production. Variations in these characteristics may occur.