



## 16000LV Automatic Transmission Fluid LV

Document version: May 6, 2024



### Description

This premium synthetic 'Low Viscosity' automatic transmission oil with very good thermal and oxidation stability. The high quality base oil with a well-balanced additive package provides reduced friction properties and optimal shifting performance. This automatic transmission oil provides excellent fuel economy.

### According to the specifications of

Aisin Warner JWS 3324  
Ford Mercon LV / WSS-M2C938-A  
Honda DW-1  
Mitsubishi Dia Queen ATF J3 / Dia Queen ATF-PA  
Toyota Fluid WS  
VW G 055 540

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001LV	1 L	6	450
16004LV	4 L	4	112
16020LV	20 L	1	30
16060LV	60 L	1	6
16205LV	205 L	1	2
16999LV	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Colour	red		
Kinematic Viscosity at 40°C	29.4	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	6.1	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	162		ASTM D92
Dynamic Viscosity at -20°C	9500	mPa.s	ASTM D5293
Flashpoint COC	210	°C	ASTM D92
Pourpoint	-45	°C	ASTM D97

These characteristics are typical of current production. Variations in these characteristics may occur.