



# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Issue date: 11-4-2011 Revision date: 3-3-2020 Supersedes: 4-2-2015 version: 3.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip  
Product code : 14000LS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

MPM International Oil Company  
Cyclotronweg 1  
2629 HN Delft - Nederland  
T +31 (0)15 2514030  
[pvhoorn@mpmoil.com](mailto:pvhoorn@mpmoil.com) - [www.mpmoil.com](http://www.mpmoil.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] [Show CLP information + DPD classification in section 2.1](#)

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available.

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P273 - Avoid release to the environment.  
P501 - Dispose of Contents and container to an approved waste disposal plant.  
EUH-statements : EUH208 - Contains: Long chain alkyl amine, Long chain alkyl dithiothiadiazole. May produce an allergic reaction.

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oleylamine	CAS-No.: 112-90-3 EC-No.: 204-015-5	> 0,1 – < 0,49	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Long chain alkyl amine	CAS-No.: 68955-53-3 EC-No.: 273-279-1 REACH-no: 01-2119456798-18	> 0,1 – < 0,49	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=0)
Alkyl phosphate	CAS-No.: 190454-07-0 EC-No.: 696-070-0	> 0,1 – < 0,49	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Long chain alkyl dithiothiadiazole	EC-No.: Conf.	> 0,1 – < 0,24	Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General	: If medical advice is needed, have product container or label at hand.
After inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
After skin contact	: Gently wash with plenty of soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: Do NOT induce vomiting. Rinse mouth. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray, powder, foam and CO<sub>2</sub>.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.  
Other information : Exercise caution when fighting any chemical fire.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and gloves.

##### 6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

No additional information available.

#### 6.4. Reference to other sections

No additional information available.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all unnecessary exposure. Ensure good ventilation of the work station.  
Handling temperature : < 40 °C  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage temperature : < 40 °C  
Storage area : Keep in a cool, well-ventilated place. Store in a closed container.

#### 7.3. Specific end use(s)

No additional information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

No additional information available.

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.1.2. Recommended monitoring procedures

No additional information available.

### 8.1.3. Air contaminants formed

No additional information available.

### 8.1.4. DNEL and PNEC

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m<sup>3</sup> oilspray (TWA, 8 hour workday) is recommended.

### 8.1.5. Control banding

No additional information available.

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Technical measures:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Safety glasses.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety goggles

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear suitable gloves resistant to chemical penetration

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	>0,35		

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

#### 8.2.2.4. Thermal hazards

No additional information available.

### 8.2.3. Environmental exposure controls

No additional information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Oily.  
Colour : Amber.

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Odour	: Characteristic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: > 200 °C ASTM D92
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: No data available.
Relative vapour density at 20°C	: No data available.
Relative density	: No data available.
Density	: 905 kg/m <sup>3</sup>
Solubility	: No data available.
Log Pow	: No data available.
Viscosity, kinematic	: 345 mm <sup>2</sup> /s @40C
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: 1 – 6 vol %

### 9.2. Other information

No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal conditions.

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

No additional information available.

### 10.4. Conditions to avoid

None under normal conditions.

### 10.5. Incompatible materials

Oxidizing agent. Acids and bases.

### 10.6. Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, nitrogen oxides (NO<sub>x</sub>), NH<sub>3</sub>, sulphur compounds.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Oleylamine (112-90-3)

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Long chain alkyl amine (68955-53-3)</b>	
LD50 oral rat	612 mg/kg
LD50 dermal rat	251 mg/kg
LC50 Inhalation - Rat [ppm]	157 ppm/4h
ATE CLP (oral)	612 mg/kg bodyweight
ATE CLP (dermal)	251 mg/kg bodyweight
ATE CLP (gases)	157 ppmv/4h
ATE CLP (vapours)	0,5 mg/l/4h
ATE CLP (dust,mist)	0,05 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>Oleylamine (112-90-3)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>Long chain alkyl amine (68955-53-3)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
<b>Oleylamine (112-90-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Long chain alkyl amine (68955-53-3)</b>	
LOAEL (dermal, rat/rabbit, 90 days)	60 mg/kg bodyweight OECD 410
NOAEL (dermal, rat/rabbit, 90 days)	20 mg/kg bodyweight OECD 410
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip</b>	
Viscosity, kinematic	345 mm <sup>2</sup> /s @40C

## SECTION 12: Ecological information

### 12.1. Toxicity

General	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

<b>Long chain alkyl amine (68955-53-3)</b>	
LC50 fish 1	1,3 mg/l <i>Oncorhynchus mykiss</i>
EC50 Daphnia 1	0,24 – 6 mg/l <i>Daphnia magna</i>
EC50 72h - Algae [1]	0,44 mg/l <i>Pseudokirchneriella subcapitata</i>

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Long chain alkyl amine (68955-53-3)

NOEC chronic fish	0,078 mg/l Oncorhynchus mykiss @ 96d
-------------------	--------------------------------------

### 12.2. Persistence and degradability

#### MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

### 12.3. Bioaccumulative potential

No additional information available.

### 12.4. Mobility in soil

No additional information available.

### 12.5. Results of PBT and vPvB assessment

No additional information available.

### 12.6. Other adverse effects

Additional information : Insoluble in water.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste materials : Empty the packaging completely prior to disposal.

## SECTION 14: Transport information

In accordance with ADR / IMDG

### 14.1. UN number

UN-No. : Not applicable  
UN-No. (IMDG) : Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : Not applicable

#### IMDG

Transport hazard class(es) (IMDG) : Not applicable

### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 14.6. Special precautions for user

#### Overland transport

No data available.

#### Transport by sea

No data available.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### 15.1.2. National regulations

No additional information available.

### 15.2. Chemical safety assessment

No additional information available.

## SECTION 16: Other information

### Full text of H- and EUH-statements

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains: Long chain alkyl amine, Long chain alkyl dithiothiadiazole. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.



# MPM Gear Oil 85W-140 GL-5 Mineral Limited Slip

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements	
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

### SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.