



# 18000VW Gearbox Oil 75W GL-4 Premium Synthetic

Document version: 11 May 2024



## Description

This premium synthetic SAE 75W VW FE transmission oil has been developed for use in VW manual transmissions, among others, and for those applications for which manufacturers require a SAE 75W GL-4 specification.

## Application manual

## According to the specifications of

API GL-4+  
BMW MTF LT-2 / MTF LT-3 / MTF LT-5  
Fiat 9.55550-MZ2  
Ford WSD-M2C200-D2 / WSD-M2C200-D3 / WSD-M2C200-E1  
Jaguar/Land Rover STJLR GX73-M1R564-AA  
Nissan 32001 1BY0A / LV MTF-1  
Opel/GM 1940004  
PSA 9730 A8  
Toyota 08885-81001 / 08885-81081  
VW G 055 512  
VW G 052 171 / 052 178 / 052 512 / 052 527 / 052 549 / 052 726 / 052 798 / 055 726 / 060 726 / 070 726  
Volvo 1161838 / 1161839

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
18001VW	1 L	6	450
18004VW	4 L	4	112
18020VW	20 L	1	30
18060VW	60 L	1	12
18205VW	205 L	1	2
18999VW	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	
Viscosity	75W		
Kinematic Viscosity at 40°C	29.93	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	6.31	mm <sup>2</sup> /s	
Viscosity Index	169		ASTM D2270
Flashpoint COC	210	°C	
Pourpoint	-42	°C	
Brookfield Viscosity at -40°C	13800	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.