



38000TA Transmission Drive Train Oil 10W

Document version: 11 May 2024



Description

The transmission drive train oil is an oil specially developed for use in 'Power Shift' transmissions, differentials and final drives, clutches and wet brakes, hydraulic systems of earth-moving equipment that meets the Caterpillar TO-4 or Allison C-4 requirements.

According to the specifications of

Allison C4
Caterpillar TO-4
Komatsu KES 07.868.1

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 38020TA | 20 L | 1 | 30 |
| 38060TA | 60 L | 1 | 6 |
| 38205TA | 205 L | 1 | 2 |
| 38999TA | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|-------|--------------------|
| Density at 15°C | 0.88 | kg/l |
| Viscosity | 10W | |
| SAE | 10W | |
| Kinematic Viscosity at 40°C | 40.8 | mm ² /s |
| Kinematic Viscosity at 100°C | 6.8 | mm ² /s |
| Viscosity Index | 106 | |
| Dynamic Viscosity at -25°C | 6000 | mPa.s |
| Flashpoint COC | 214 | °C |
| Pourpoint | -30 | °C |
| Total Base Number | 7.9 | mgKOH/g |

These characteristics are typical of current production. Variations in these characteristics may occur.