



43000 2-Stroke Oil Semi Synthetic Scooter Selfmix

Document version: 11 May 2024



Description

MPM 2-Stroke Semi Synthetic Scooter selfmix oil has been specially developed and is therefore suitable for use in modern air- or water-cooled 2-stroke street legal scooter engines. This oil is self-mixing and suitable for engines with oil-injection systems. The engine oil provides high performance and protection against wear on the engine and pistons. This oil has the low smoke specification for driving in city areas.

Note: **Not for competition use.**
Suitable for use in oil-injection systems.

According to the specifications of

API TC / TC+
ISO L-EGD
JASO FC (low smoke) / FD (low smoke)
Piaggio SL
TISI

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
43001	1 L	6	450
43005	5 L	4	112
43020	20 L	1	30
43060	60 L	1	6
43205	205 L	1	2
43999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.870	kg/l	ASTM D4052
Colour	Dark Green		VISUAL
Kinematic Viscosity at 40°C	76.8	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	10.4	mm ² /s	ASTM D445
Viscosity Index	120		ASTM D2270
Flashpoint COC	106	°C	ASTM D92
Total Base Number	1.7	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.