



86000A Antifreeze Premium Longlife G12+ Concentrate

Document version: 11 May 2024



Description

This Long Life OAT silicate-free antifreeze is of very high quality and has been specially developed for protection of non-ferrous metals such as aluminium and magnesium. This antifreeze should be diluted with the recommended quantity of water before use.

According to the specifications of

ASTM D3306
DAF 74002
Ford ESE-M97B49-A / WSS-M97B44-C / WSS-M97B44-D
GM/Opel 1940 656 / 6277M
MAN 248 / 324 SNF
MB 325.3
Paccar 74002
Renault 41-01-001
VW TL 774D G12+ / 774F G12+
Volvo No. 260 / VCS

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
86001A	1 L	6	450
86005A	5 L	4	112
86020A	20 L	1	30
86060A	60 L	1	6
86205A	205 L	1	2
86999A	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.12	kg/l
Colour	red	
Freezing Point 50% diluted	-40	°C
Ph 50% diluted	7.6	
Water	3.72	mass%
Copper Corrosion	5.3	

These characteristics are typical of current production. Variations in these characteristics may occur.